

iGATE T203-HD

DVB-T2 Set-top Box

iGate T203-HD is a DVB-T2 Set-top Box supports 1080P full HD output to bring customer a smooth video experience with a rich range of free TV contents using VHF/UHF band broadcasting.



PRODUCT HIGHLIGHTS

- Scheduled and manual recording
- Time-shift Mode
- Next seven-day program guide
- Convenient channel tuning and management

FEATURES

EPG

- Service name, Program title, Description, Now/ Next event
- EPG organizer to access Next seven-day program guide

Channel Management

- Automatic channel change recognition
- Auto scan - Manual scan - Only FTA scan
- Convenient channel management: number, order, search, skip, lock, categorize and select favorite channel

Recording

- Scheduled or manual recording (PVR)

Time-shift

- Time-shift supported

Service

- Multi-Language Subtitling supported
- Languages and Fonts: English, Vietnamese
- Schedule on/off
- Child lock
- Signal Strength and Quality Bar

Multimedia

- Audio, video and photo play from external storage device

Software Upgrade

- OTA & USB Software Upgrade

TECHNICAL SPECIFICATIONS

RF

Radio 174MHz ÷ 790MHz

Frequencies

Signal 8 MHz

bandwidths

Antenna SISO, MISO; active and passive

PLP Support M-PLP & Common PLP

CAS Supported




Operation in SFN & MFN Supported SFN & MFN

Video/Audio

Output Max 1080p@50fps

Aspect Ratio	4:3, 16:9		1x S/PDIF
Video	MPEG-2 SD, MPEG-4		1x HDMI 1.4
Decoding	SD, MPEG-4 HD, H.264	USB	1x USB 2.0
Audio	MPEG-1 Layer II	Power	
Decoding	HE-AAC Level 2, 4 32, 44.1, 48kHz	Adapter	Input: 90VAC ÷ 260 VAC; f = 48Hz ÷ 63Hz Output: 12VDC - 1.25A
Connectors			
RF	1x Input Connector (75 Ω, IEC female type) 1x Output Connector (75 Ω, IEC male type with loop-back)	Operating temperature and humidity	
AV	1x RCA 2x L/R	Operator	< 95%
		Humidity	
		Operation	0°C ÷ 40°C
		Temperature	

CUSTOMER CARE & TECHNICAL SUPPORT CENTRE

-  **Address:** 1st floor, VNPT Technology Building, No. 124, Hoang Quoc Viet Str., Cau Giay Dist., Hanoi, Vietnam
-  **Telephone:** +84.24.3750.6666 (24/7)
-  **Email:** support@vnpt-technology.vn